

Wall Light

WLMFC64LED 64 Watt LED Wall Light









3000K or warmer CCTs only

SPECIFICATIONS

SFECIFICATIONS.						
	WLMFC64LED3K	WLMFC64LED				
Lumens:	7,776	8,131				
Watts:	62.69	61.82				
Lumens/Watt:	124.0	131.5				
CRI:	81	81.9				
CCT:	3096	4560				
DLC Prod. ID:	P47CDRKC	PWVBFGJ6V				

Construction:

Rugged Traditional aluminum die cast housing provides proven environmental protection for LED modules. Traditional fixture design provides a familiar look and standard installation requirements. Retaining this look allows the ability to upgrade fixtures gradually, while retaining the same overall fixture appearance throughout a facility.

Glare Free:

Positioning of the LED modules within the housing result in light directed to desired locations and eliminates offensive light.

Thermal Management:

Atlas' Patent Pending exclusive Thermal Management System[™] features a unique internal design that allows for lower operating temperatures which results in a brighter, whiter light, more stable color and longer LED and driver life.

Listings:

Luminaire is certified to UL/cUL Standards for Wet Locations DesignLights Consortium Premium qualified luminaire, eligible for rebates from DLC member utilities.

AC Input:

120/208/240/277 V

Driver:

Constant current, Class 2, 120-277 VAC, 50-60 Hz High Efficiency – min. 84% Off-State Power: 0 Watts 0-10 V Dimming

LEDs:

3000K | 4500K CCT Epoxy Guard[™] protective conformal coated boards Atlas LEDs provide higher lumen output, greater energy efficiency and more reliable fixture performance.

Warranty:

Atlas Lighting Products provides a 5 year limited warranty for this product. A full warranty can be found at www.alpinc.com.

Testing:

Atlas LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 & LM-80, and have received the Department of Energy "Lighting Facts" label.

Installation:

Fixture retains the same knock-out sizes and positions as previous models, reducing wiring costs.

Photo Control:

For factory installed 120V button photo control add suffix PC to part number.

Emergency Back-up:

For factory installed Emergency Back-Up add suffix EB to part number.


¹LED Life Span Based Upon LM-80 Test Results

ATLAS LIGHTING PRODUCTS, INC.

PO BOX 2348 | BURLINGTON, NC 27216 800-849-8485 | FAX: 1-855-847-2794 | www.atlasled.com

Rebates and Incentives are available in many areas. Contact an Atlas Representative for more information.

*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components. Meets Buy American requirements within the ARRA.




ixture Type 64 Watt LED Wall Light

Catalog Number WLMFC64LED

Approved by




DIMENSIONS:





WLMFC64LED 64 Watt LED Medium Wall Light

PHOTOMETRIC



ENERGY SAVINGS

LE	D	HID			
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
64	\$28	200	232	\$128	\$100
64	\$28	250	285	\$150	\$122
64	\$28	400	458	\$226	\$198

MOUNTING DETAIL

