

WSPS20LED

20 Watt LED SlimPak Pro

REPLACES UP TO 100W MH



- 2,228 **LUMENS**
- 20 **WATTS**
- 109 **LPW**
- 75 **CRI**
- 4500K **CCT**
- 0-10V **DIMMING**
- REC MNT HT**
8 FT to 10 FT



Patent Pending

- Slim Low Profile Design
- Attractive Architectural Styling
- Quick and Easy Mounting
- Bottom Hinged to Prevent Leakage


6"Wx7.65"Hx4"D
3.8 LBS

ORDERING INFORMATION

CATALOG #	DESCRIPTION	CCT	REPLACES UP TO	VOLTS
WSPS20LED	20W LED SlimPak Pro	4500K	100W MH	120-277

Specs shown are for 4500K CCT. Also available in 3000K, 4000K and 5000K. See Cut Sheet for more information.

FOOTCANDLES ON THE GROUND



	8' Mtg Height		10' Mtg Height	
	90°	45°	90°	45°
0'	19.2	19.2	12.0	12.0
5'	15.7	11.8	11.2	9.1
10'	5.0	3.8	5.0	4.0
15'	1.4	1.3	2.1	1.7
Average 7.5		Average 6.0		

OPTIONS

ADD SUFFIX #	DESCRIPTION	ADD SUFFIX #	DESCRIPTION
PC	120V Photocontrol	PM	208-277V Photocontrol

ENERGY SAVINGS

LED		HID			
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
20	\$9	50	72	\$52	\$43
20	\$9	70	90	\$59	\$50
20	\$9	100	129	\$77	\$68

QUICK & EASY INSTALLATION



1 Unscrew door with Phillips screw driver.



2 Using the leveling bubble in the wall mounting box, level the fixture & attach to wall.



3 Secure door to back box with hinge. Complete wiring. Tighten door with screws.



*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components

