

WSPS40LED

40 Watt LED SlimPak Pro

REPLACES UP TO 175W MH



- Slim Low Profile Design
- Attractive Architectural Styling
- Quick and Easy Mounting
- Bottom Hinged to Prevent Leakage

Patent Pending



6"Wx7.65"Hx4"D
3.8 LBS

4,047 **LUMENS**

40 **WATTS**

106 **LPW**

75 **CRI**

4500K **CCT**

0-10V **DIMMING**


REC MNT HT
12 FT to 14 FT

ORDERING INFORMATION

CATALOG #	DESCRIPTION	CCT	REPLACES UP TO	VOLTS
WSPS40LED	40W LED SlimPak Pro	4500K	175W MH	120-277

Specs shown are for 4500K CCT. Also available in 3000K, 4000K and 5000K. See Cut Sheet for more information.

FOOTCANDLES ON THE GROUND



	12' Mtg Height		14' Mtg Height	
	90°	45°	90°	45°
0'	14.7	14.7	10.6	10.6
5'	14.8	12.5	11.1	9.7
10'	8.3	6.8	7.3	6.1
15'	4.3	3.3	4.3	3.4
Average	8.4		6.9	

OPTIONS

ADD SUFFIX #	DESCRIPTION	ADD SUFFIX #	DESCRIPTION
PC	120V Photocontrol	PM	208-277V Photocontrol

ENERGY SAVINGS

LED		HID			
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
40	\$18	100	129	\$77	\$59
40	\$18	150	185	\$100	\$82
40	\$18	175	210	\$112	\$94

QUICK & EASY INSTALLATION



Unscrew door with Phillips screw driver.



Using the leveling bubble in the wall mounting box, level the fixture & attach to wall.



Secure door to back box with hinge. Complete wiring. Tighten door with screws.



*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components

